

## Leveling Agent GLP1202

### I Description

Leveling Agent GLP1202 is a polyacrylate with silica carrier. It has excellent leveling performance and high DOI (Distinctness of Image). GLP1202 can be used in all system of powder coatings.

### II Technical data

GLP1202	Test Method	Specification
Appearance	Visualization	White granules
Active Ingredient	GB/T 7531-2008	≥65%
Solid Content	GB/T 1725-2008	≥99%

### III Application

1. GLP1202 helps to reduce surface tension of the film, eliminate the pinhole and eye-fishes effectively.
2. GLP1202 has good wettability for the substrate and provide high film DOI.
3. GLP1202 does not contain silicone, so it has no interference and does not affect recoating adhesion.
4. As free flow powder, it's easily incorporated into powder coating formulation by standard blend operation and homogenized with resin and other components to form a uniform system.
5. The dosage of GLP1202 in formulation is about 0.5~1.5%wt.

### IV Package, Storage & Handling

Available in polyethylene-lined, multi-ply paper bags, N.W.20KGS/Bag.

Keep in the cool and dry place, keep away from fire.

*Notice: The key technical data or specifications for the above product described in this paper may be changed from time to time due to improvement constantly. SSC reserves the right to change the specifications of its products without prior notice. Although the information in this paper is based on our own investigation and is believed reliable, SSC cannot assume any responsibility for performance or results obtained through the use of our products herein described. Neither we nor our agents shall be liable for any injury, loss or damages directly or indirectly caused by our products. The user is held to check the quality, safety and all other properties of our product before using. Nothing herein is to be taken as permission or recommendation to practice any patented invention without a license.*

